



C696G
 Formerly LIN-326926-A

Fallstop® adjustable lanyard is designed to be used as a connecting device in a personal work positioning or travel restraint system. The lanyard connects the user's harness to an anchorage point, anchorage connector or a rope grab / fall arrester. Fallstop® adjustable web lanyard is made of 1 inch (25 mm) wide by 3 /16 inch (5 mm) thick nylon webbing that provides wear resistance. The lanyard length is adjustable from 3 to 6 ft. (0.9 to 1.8 m) to adapt to different job conditions.

Features include:

- improved handling;
- greater resistance to wear;
- contrary to rope, the web is not subject to unraveling;
- ease of adjustment compared to rope.

Applicable standards:

- ANSI Z359.1
- ANSI A10.14
- OSHA fall protection requirements
- CSA approved models are available with forged components.

Applications:

- Work positioning
- Restraint

⚠WARNING The anchorage point location in combination with lanyard length should never permit a free fall distance of more than 6 feet (1.8 m). Consult local regulations as permitted free fall distance may be less than 6 feet.

⚠WARNING A 6-foot fall with a web lanyard will generate an impact force up to 1,800 lbs. (8 kN), keep lanyard as short as possible to reduce risks of serious injury.

Available models:

C696G 6 ft. adjustable web lanyard with a 3/4 in. double-locking snap hook at both ends

C696E 6 ft. adjustable web lanyard with a 3/4 in. double-locking snap hook one end and a 2 1/4 in. double-locking snap hook at the other end

For more information on the choice of connectors offered by Tractel, refer to technical sheet T-4536.

For further information refer to the "Use and Maintenance Instructions" for lanyards.

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Webbing	Nylon webbing Width: 1 in. (25 mm) Thickness: 3/16 in. (5 mm) Tensile strength: 9,000 lbs. (40 kN) Webbing is heat-cut to prevent fraying.	ANSI Z359.1
Stitching	Lanyard is lock-stitched Thread #346	
3/4 in. double-locking snap hook	Constructed of die-cut steel, zinc plated Tensile strength: 5,000 lbs. (22 kN)	ANSI Z359.1
2 1/4 in. double-locking snap hook	Constructed of die-cut steel, zinc plated Tensile strength: 5,000 lbs. (22 kN)	ANSI Z359.1
Adapter	Constructed of drop-forged steel, zinc plated Tensile strength: 4,000 lbs. (17 kN)	ANSI Z359.1
Capacity	310 lbs. (140 Kg) One person	