



The anchor sling, wrapped around a beam, provides an anchorage attachment point capable of supporting a load of 10,000 lbs. (44 kN).

An extra piece of webbing is fixed on the entire length of the sling to protect it from sharp edges and to prolong its life. Where edges are extremely sharp, it is recommended to use pads.

WARNING Always select an anchorage point that is rigid and capable of supporting 5,000 lbs. (22 Δ kN) per person attached.

WARNING

Δ Applicable standards:

- Meet CSA, ANSI and OSHA anchorage requirements.

Available models:

V41310 3-foot (0.9 m) anchor sling, rated 10,000 lbs. (44 kN)

V41610 6-foot (1.8 m) anchor sling, rated 10,000 lbs. (22 kN)

PARTS	SPECIFICATIONS
Webbing (sling)	Nylon webbing Width: 3 in. (76 mm) Thickness: 0.09 in. (2 mm) Tensile strength: 17,500 lbs. (77 kN) Webbing is heat-cut to prevent fraying.
Webbing (protective)	Polyester webbing Width: 4 in. (102 mm) Thickness: 0.08 in. (2 mm) Webbing is heat-cut to prevent fraying.
Stitching	Sling is lock-stitched Thread #207, #346
Hoist link 2 in.	Constructed drop-forged alloy steel, chromate finish Proof load: 12,000 lbs. (53 kN) Breaking strength: 24,000 lbs. (107 kN)
Hoist link 3 in.	Constructed of drop-forged alloy steel, chromate finish Proof load: 10,000 lbs. (44 kN) Breaking strength: 24,000 lbs. (107 kN)
Capacity	310 lbs. (140 Kg) per person Two persons