



The Gripgrab® is a cam lever single jaw grab designed to move freely along a synthetic lifeline. The rope grab protects the worker while climbing up and down.

**Features include:**

- Construction
  - Housing: stainless steel 303, 304
  - Internal swing cam: stainless steel, alloy
  - Roller: plastic
- Features a 2-inch (51 mm) diameter ring to reduce the possibility of disengagement of the snap hook.
- Breech loading anywhere along lifeline.
- Roller positions grab easily anywhere on lifeline.
- Fits 3/4 in. (19 mm) rope diameter lifeline.
- Capacity is 310 lbs. (140 kg), one person including clothing and tools.

For further information refer to the "Use and Maintenance Instructions" for Gripgrab® rope grab.

**Recommended types of lifeline:**

3/4 in. (19 mm) diameter

- polypropylene 3 strands
- nylon 3 strands
- polyblend (combination of polypropylene and polyester) 3 strands
- superline (combination of polypropylene and polyethylene) 3 strands

**DO NOT USE ON PROHIBITED LIFELINES SUCH AS  
MANILA OR COTTON ROPE OR, ANY TYPE OF NATURAL ROPE.**

**Applications:**

- scaffolding structures
- suspended stages
- climbing ladders

**Applicable standards:**

- CSA Z259.2
- ANSI Z359.1
- ANSI A10.14
- OSHA fall protection requirements
- New York BSA approved