

BB850M
 Formerly LIN-30485M-A

This Tractel basic safety belt is made from two plies of 1 3/4 in. nylon webbing but is also available in polyester (BB851M) and safe-set polyester (BB852M).

Features include:

- tongue & buckle attachment only;
- compatible with all Fallstop harnesses with the exception of the Ultra-Light model (A030M);
- large die-cut D-ring(s) on two models;
- mylar label.

Sizes:

Small	30 – 34 in.	(76 – 86 cm)	BB850S
Medium	34 – 38 in.	(86 – 96 cm)	BB850M
Large	38 – 42 in.	(96 – 106 cm)	BB850L
X-large	42 – 48 in.	(106 – 122 cm)	BB850XL

Applicable standards:

- ANSI Z359.1
- ANSI A10.14
- OSHA fall protection requirements
- CSA approved models are available with forged components

⚠ WARNING

Since January 1st, 1998, waist belts have been prohibited for fall arrest.

For further information refer to "Use and Maintenance Instructions" for harnesses and belts.

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Standard webbing	Nylon webbing Width: 1 3/4 in. (45 mm) Thickness: 0.08 in. (2 mm) Tensile strength: 6,000 lbs. (27 kN) Webbing is heat-cut to prevent fraying.	ANSI Z359.1
Optional webbing	Polyester webbing Width: 1 3/4 in. (45 mm) Thickness: 0.07 in. (1.7 mm) Tensile strength: 7,000 lbs. (31 kN) Webbing is heat-cut to prevent fraying.	ANSI Z359.1
Optional webbing	Safe-set polyester webbing Width: 1 3/4 in. (45 mm) Thickness: 0.07 in. (1.7 mm) Tensile strength: 5,600 lbs. (25 kN) Webbing is heat-cut to prevent fraying.	
Stitching	Belt is lock-stitched Thread #346	
D-ring	Constructed of die-cut steel, zinc plated Proof loaded 100% at 3,600 lbs. (16 kN) Tensile strength: 5,000 lbs. (22 kN)	ANSI Z359.1
Tongue & buckle	Constructed of drop-forged steel, zinc plated Tensile strength: 4,000 lbs. (17 kN)	ANSI Z359.1
Grommets	Grommets are made of copper.	
Plastic loops	Each webbing strap with a free end has keeper loops.	
Capacity	310 lbs. (140 Kg) One person	


Webbing options

The 1 3/4 in. wide belt is offered in three types of webbing to meet specific requirements.

- BB850M** Nylon webbing, gray: standard.
- BB851M** Polyester webbing, gray: recommended where chemical environment is hostile to nylon.
- BB852M** Safe-set polyester, black: recommended where chemical environment is hostile to nylon.


Modular capability

The 1 3/4 in. wide belt can be ordered with different combinations of attachment points for specific applications.




no D-ring

- BB830M** No D-ring
Tool belt



Single centered D-ring

- BB840M** Single centered D-ring
Travel restraint applications



side positioning D-rings

- BB850M** Side positioning D-rings
Work positioning